



G Jib

The G Jib combines all the attributes of the perfect jib arm: ultra-lightweight, short back end and able to handle a remote head and full-sized camera package. The G Jib was designed to get just above a standing person with an under slung head, yet also scrape the floor. It has integrated dolly wheels that are easily spun around the axis of the never flat tires for quick track access or that can swing out the leveling jacks to secure the base for a static shot. The G Jib can be used on its proprietary base or mounted on either a Mitchell or euro mount to any dolly. Its single piece construction makes it possible to be built in literally minutes by one person.



G Jib

G Jib Quick Specs

Maximum height to leveling head	8'	2.4m
Minimum height to leveling head	11"	0.28m
Arm length	8'2"	2.5m
Fulcrum to leveling head	5'8"	1.7m
Fulcrum to weight bucket	2'6"	0.8m
Height from ground to fulcrum	3'10"	1.2m
Base width	2'9"	0.8m
Base length	3'11"	1.2m
Maximum camera payload	125lbs	57kg



WILLIAM F. WHITE INTERNATIONAL INC.

A Comweb Group Member

www.whites.comwww.whites.comwww.whites.comwww.whites.comwww.whites.com

VANCOUVER • CALGARY • EDMONTON • REGINA • WINNIPEG • TORONTO • OTTAWA • MONTREAL • HALIFAX • BUDAPEST, HU

Partners in Production®