



# Mega III

The Mega III is a light-weight, highly rigid, three-axis digital remote head. It is capable of accepting the vast majority of film and HD cameras. With slirings in all three axis the Mega III can swiftly maneuver a 35mm camera with a large zoom lens without the restriction of snagging loose wires. Arriflex, Panaflex, and 16mm Arri cameras are rigged in a nodal position for perfect "corkscrew" rolls. An intuitive touch screen display allows the operator to adjust the speed, dampening, end stops, soft stops, recording, playback, and more. The Mega III boasts one of the finest operational feel, assisted by zero-backlash gearboxes and encoders that check their position 300 times/sec to ensure the utmost accuracy.



### Mega III Features

- Precise digital control
- Independent soft stops for each axis
- Course & fine positional indicator for operator
- Slirings in each axis
- Arri 435 to 150fps through system
- Adjustable wheel response
- Simple touch-screen control
- Record/playback facilities
- User-settable playback speed

### Mega III Quick Specs

Weight	35kg (75lbs)
Max Pan/Tilt/Roll Speed	180°/sec
Encoder Counts/Rev	Pan/Tilt 1mil. Roll 570,000
Camera Movement	Three wheels
Input/Display System	Touchscreen + EL Display
Record Time	Standard: 52 sec Extended: 100 sec
Power Requirements	20-32 VDC 90-240 VAC



WILLIAM F. WHITE INTERNATIONAL INC.

A Comweb Group Member